

Technische eigenschappen **Purfect**

TECHNISCHE EIGENSCHAPPEN / TECHNICAL PROPERTIES

Samenstelling / Composition	100% Polyurethaan / 100% Polyurethane
Onderlaag / Backing	Katoen / Cotton
Gewicht / Weight	595 g/m ² ± 30 g/m ²
Breedte / Width	140 cm
Rollengte / Roll length	30 lm
Dikte / Thickness	1.00 mm ± 0,10 mm

		<i>Normen/ standards</i>
Trekweerstand / Tensile strength	> 30 daN / 5 cm > 22 daN / 5 cm	ISO 1421
Scheurweerstand / Tear strength	> 2.2 daN > 2.0daN	ISO 4674-01
Wrijvingsweerstand / Abrasion resistance	> 500.000	EN ISO 5470-2 Martindale
Naadweerstand / Seam resistance	> 16 daN / 5cm > 16 daN / 5cm	ISO 13936-1
Uitrekking bij belasting 30N/5cm / Elongation under 30N/5cm	> 11% - 18%	ISO 1421
Hechtingsweerstand / Coating to fabric adhesion	> 3 daN / 5 cm	ISO 2411
Kleurvastheid / Colour light fastness	> 6	EN ISO 105 B02
Wrijftechtheid veslic (behandeld met 70% ethanol) Rub fastness veslic (70% ethanol treatment)	Grade 4/5	ISO 11640
Kleurvastheid bij transpiratie / Colour fastness to perspiration	Grade 4	ISO 11641
Hydrolysis / Hydrolyse test (10 weeks)	Geslaagd / Pass	
Weerstand tegen bloed & urine / Surface restistance against blood and urine	Geslaagd / Pass	EN 12720
Oeko-tex	100	Class 1
Brandveiligheid / Flame retardancy	BS 5852 EN 1021 DIN 4102-1B2 IMO 2010 FTP code	Crib 5 1 & 2 B2 Annex 1 - Part 8
Kwaliteit / Quality		ISO 9001
Milieumanagement / Environmental management		ISO 14001

